

Asset Management Plan

Township of Chamberlain

Table of Contents

| 1 | Intro | oduction | 5 |
|---|-------|---|----|
| | 1.1 | Overview | 5 |
| | 1.2 | Legislative Context for the Asset Management Plan | 7 |
| | 1.3 | Asset Management Plan Development | 8 |
| | 1.4 | Maintaining and Integrating the Asset Management Plan | 8 |
| 2 | Stat | e of Local Infrastructure and Levels of Service | 9 |
| | 2.1 | Introduction | 9 |
| | 2.2 | Roads | 10 |
| | 2.2. | 1 State of Local Infrastructure | 10 |
| | 2.2. | 2 Condition | 11 |
| | 2.2. | 3 Current and Proposed Levels of Service | 15 |
| | 2.3 | Bridges and Structural Culverts | 18 |
| | 2.3. | 1 State of Local Infrastructure | 18 |
| | 2.3. | 2 Condition | 19 |
| | 2.3. | 3 Current Levels of Service | 21 |
| | 2.3. | 4 Proposed Levels of Service | 22 |
| | 2.4 | Road Culverts | 23 |
| | 2.4. | 1 State of Local Infrastructure | 23 |
| | 2.4. | 2 Condition | 25 |
| | 2.4. | 3 Current Levels of Service | 27 |
| | 2.4. | 4 Proposed Levels of Service | 27 |
| | 2.5 | Railway Crossings | 29 |
| | 2.5. | 1 State of Local Infrastructure | 29 |
| | 2.5. | 2 Condition | 29 |
| | 2.5. | 3 Current Levels of Service | 30 |
| | 2.5. | 4 Proposed Levels of Service | 31 |
| | 2.6 | Facilities | 33 |
| | 2.6. | 1 State of Local Infrastructure | 33 |
| | 2.6. | 2 Condition | 33 |
| | 2.6. | 3 Current Levels of Service | 34 |
| | 2.6. | 4 Proposed Levels of Service | 35 |
| | 2.7 | Vehicles and Equipment | 37 |

| | 2.7.1 | State of Local Infrastructure | 37 |
|---|-----------|-------------------------------|----|
| | 2.7.2 | Condition | 38 |
| | 2.7.3 | Current Levels of Service | 39 |
| | 2.7.4 | | 40 |
| | 2.7.5 | Proposed Levels of Service | 40 |
| | 2.8 Sigr | ns | 41 |
| | 2.8.1 | State of Local Infrastructure | 41 |
| | 2.8.2 | Condition | 41 |
| | 2.8.3 | Current Levels of Service | 42 |
| | 2.8.4 | Proposed Levels of Service | 42 |
| 3 | Lifecycle | Management Strategy | 43 |
| | 3.1 Intr | oduction | 43 |
| | 3.2 Roa | ads | 43 |
| | 3.2.1 | Lifecycle Activities | 43 |
| | 3.2.2 | Degradation Profiles | 44 |
| | 3.2.3 | Expected Lifecycle | 45 |
| | 3.2.4 | Capital Costs / Forecast | 45 |
| | 3.3 Brid | dges and Structural Culverts | 46 |
| | 3.3.1 | Lifecycle Activities | 46 |
| | 3.3.2 | Degradation Profiles | 46 |
| | 3.3.3 | Decision Criteria | 46 |
| | 3.3.4 | Expected Life | 47 |
| | 3.3.5 | Capital Costs / Forecast | 48 |
| | 3.4 Fac | ilities | 49 |
| | 3.4.1 | Lifecycle Activities | 49 |
| | 3.4.2 | Degradation Profile | 49 |
| | 3.4.3 | Expected Lifecycle | 50 |
| | 3.4.4 | Capital Costs/Forecasts | 50 |
| | 3.5 Roa | ad Culverts | 51 |
| | 3.5.1 | Lifecycle Activities | 51 |
| | 3.5.2 | Degradation Profile | 51 |
| | 3.5.3 | Expected Lifecycle | 51 |
| | 3.5.4 | Capital Costs/Forecasts | 51 |

| | 3.6 | Sign | NS | . 52 |
|---|------|-------|---------------------------|------|
| | 3.6. | 1 | Lifecycle Activities | . 52 |
| | 3.6. | 2 | Degradation Profile | . 52 |
| | 3.6. | 3 | Expected Lifecycle | . 52 |
| | 3.6. | 4 | Capital Costs/Forecasts | .52 |
| | 3.7 | Age | Based Assets | . 53 |
| | 3.7. | 1 | Lifecycle Activities | . 53 |
| | 3.7. | 2 | Degradation Profiles | .53 |
| | 3.7. | 3 | Decision Criteria | . 53 |
| | 3.7. | 4 | Expected Lifecycle | . 53 |
| | 3.7. | 5 | Capital Costs / Forecasts | .54 |
| | 3.8 | Pop | ulation | .54 |
| 4 | Fina | ncing | g Strategy | . 55 |
| | 4.1 | Intro | oduction | . 55 |
| | 4.2 | Ann | ual Costs | . 55 |
| | 4.3 | Fun | ding Shortfall | . 58 |

| Table 1-1 | 5 |
|------------|----|
| Table 2-1 | 10 |
| Table 2-2 | 12 |
| Table 2-3 | 13 |
| Table 2-4 | 14 |
| Table 2-5 | 15 |
| Table 2-6 | 16 |
| Table 2-7 | 17 |
| Table 2-9 | 18 |
| Table 2-10 | 20 |
| Table 2-11 | 20 |
| Table 2-12 | 22 |
| Table 2-14 | 23 |
| Table 2-15 | 24 |
| Table 2-16 | 25 |
| Table 2-17 | 27 |
| Table 2-18 | 28 |
| Table 2-19 | 29 |
| Table 2-21 | 29 |
| Table 2-23 | 33 |
| Table 2-24 | 34 |
| Table 2-25 | 35 |
| Table 2-26 | 37 |
| Table 2-27 | 38 |
| Table 2-30 | 41 |
| Table 2-31 | 42 |
| Table 3-1 | 43 |
| Table 3-2 | 46 |

1 Introduction

1.1 Overview

The main objective of an asset management plan is to use a municipality's best available information to develop a comprehensive long-term plan for capital assets. In addition, the plan should provide a sufficiently documented framework that will enable continuous improvement and updates of the plan, to ensure its relevancy over the long term.


Through funding, Watson & Associates Economists Ltd. (Watson) was retained by the Province of Ontario to consult with the Municipality on this update. With this update, it is the intent to move the Municipality's asset management practices towards compliance with Ontario Regulation 588/17. It is intended to be a tool for Municipality staff and Council to use during various decision-making processes, including the annual budgeting process and future capital grant application processes. This plan will serve as a road map for sustainable infrastructure planning going forward.

The following assets are included in this asset management plan:

Table 1-1
Asset Classes and Replacement Costs

| Asset Class | Replacement Costs | | | |
|----------------------------------|-------------------|---------------|--|--|
| Roads | \$ | 20,016,511.83 | | |
| Bridges and Structural Culverts | \$ | 13,664,982.14 | | |
| Road Culverts | Culverts \$ | | | |
| Facilities (buildings and parks) | \$ | 577,764.39 | | |
| Railway Crossings | \$ | 119,000.00 | | |
| Signs | \$ | 2,650.00 | | |
| Vehicles and Equipment | \$ | 997,268.96 | | |
| Total | \$ | 35,697,279.20 | | |

Figure 1-1



The Municipality's goals and objectives with respect to asset management are identified in the Municipality's Strategic Asset Management Policy. A major theme within that policy is for the Municipality's physical assets to be managed in a manner that will support the sustainable provision of municipal services to Municipality residents. Through the implementation of the asset management plan, the Municipality's practice should evolve to provide services at levels proposed within this document. Moreover, infrastructure and other capital assets should be maintained at condition levels that provide a safe and functional environment for its residents. Therefore, the asset management plan and the progress with respect to its implementation will be evaluated based on the Municipality 's ability to meet these goals and objectives. Ultimately it is the taxpayers of the municipality that contribute to the replacement of these assets. The following table illustrates that given our small population the cost/household is very high.

Table 1-2
Asset Classes per Household

| Asset Class | | placement Costs | Households | Cos | st/Household |
|----------------------------------|----|-----------------|------------|-----|--------------|
| Roads | \$ | 20,016,511.83 | 165 | \$ | 121,312.19 |
| Bridges and Structural Culverts | \$ | 13,664,982.14 | 165 | \$ | 82,818.07 |
| Road Culverts | \$ | 319,101.87 | 165 | \$ | 1,933.95 |
| Facilities (buildings and parks) | \$ | 577,764.39 | 165 | \$ | 3,501.60 |
| Railway Crossings | \$ | 119,000.00 | 165 | \$ | 721.21 |
| Signs | \$ | 2,650.00 | 165 | \$ | 16.06 |
| Vehicles and Equipment | \$ | 997,268.96 | 165 | \$ | 6,044.05 |
| Total | \$ | 35,697,279.20 | 165 | \$ | 216,347.15 |

1.2 Legislative Context for the Asset Management Plan

Asset management planning in Ontario is continuous changing. Before 2009, capital assets were recorded by municipalities as expenditures in the year of acquisition or construction. The long-term issue with this approach was the lack of a capital asset inventory, both in the municipality's accounting system and financial statements. As a result of revisions to section 3150 of the Public Sector Accounting Board handbook, effective for the 2009 fiscal year, municipalities were required to capitalize tangible capital assets, thus creating an inventory of assets. In 2012, the province launched the Municipal Infrastructure Strategy. As part of that initiative, municipalities and local service boards seeking provincial funding were required to demonstrate how any proposed project fits within a detailed asset management plan. In addition, asset management plans encompassing all municipal assets needed to be prepared by the end of 2016 to meet Federal Gas Tax agreement requirements. To assist in defining the components of an asset management plan, the Province produced a document entitled Building Together: Guide for Municipal Asset Management Plans. This guide documented the components, information, and analysis that were required to be included in municipal asset management plans under this initiative. The province's Infrastructure for Jobs and Prosperity Act, 2015 (IJPA) was proclaimed on May 1, 2016. This legislation detailed principles for evidence-based and sustainable long-term infrastructure planning. The Infrastructure for Jobs and Prosperity Act also gave the province the authority to guide municipal asset management planning by way of regulation. In late 2017, the province introduced O. Reg. 588/17 under the Infrastructure for Jobs and Prosperity Act. The intent of O.Reg. 588/17 is to establish a standard format for municipal asset management plans. Specifically, the regulations require that asset management plans be developed that define the current and proposed levels of service, identify the lifecycle activities that would be undertaken to achieve these levels of service, and provide a financial strategy to support the levels of service and lifecycle activities. This plan has been developed to address the requirements of O. Reg. 588/17 utilizing the best information available to the Municipality at this time. With the impact of the COVID 19 pandemic the regulatory timelines associated with O. Reg 588/17 were amended as followed:

• July 1, 2022 (previously July 1, 2021): Date for municipalities to have an approved asset management plan for core assets (roads, bridges and culverts, water, wastewater and

- stormwater management systems) that identifies current levels of service and the cost of maintaining those levels of service.
- July 1, 2024 (previously July 1, 2023): Date for municipalities to have an approved asset management plan for all municipal infrastructure assets that identifies current levels of service and the cost of maintaining those levels of service.
- July 1, 2025 (previously July 1, 2024): Date for municipalities to have an approved asset management plan for all municipal infrastructure assets that builds upon the requirements set out in 2024. This includes an identification of proposed levels of service, what activities will be required to meet proposed levels of service, and a strategy to fund these activities.

1.3 Asset Management Plan Development

The asset management plan was developed using a program that leverages the Municipality's asset management principles as identified within its strategic asset management policy, capital asset database information, and staff input in identifying current and proposed levels of service, as well as proposed asset management strategies. The development of the Municipality's asset management plan is based on the steps summarized below:

- Compile available information pertaining to the Municipality's capital assets to be included in the plan, including attributes such as size/material type, useful life, age, and current valuation. Update current valuation, where required, using benchmark costing data or applicable inflationary indices.
- 2. Define and assess current asset conditions, based on a combination of Municipality staff input, existing asset reports, and an asset age-based condition analysis.
- 3. Define and document current levels of service, as well as proposed levels of service, based on discussions with Municipal Council and staff, and consideration of various background reports.
- 4. Develop an asset management strategy that provides the activities required to sustain the levels of service discussed above. The strategy summarizes these activities in the forecast of annual capital and operating expenditures required to achieve these level of service outcomes.
- 5. Develop a financing strategy to support the lifecycle management strategy. The financing plan informs how the capital and operating expenses arising from the asset management strategy will be funded over the forecast period.
- 6. Document the comprehensive Asset Management Plan in a formal report to inform future decision-making and to communicate planning to municipal stakeholders.

1.4 Maintaining and Integrating the Asset Management Plan

It should be noted, that while this report covers a forecast period of 20 years, the full lifecycle of the Municipality's assets were considered in the calculations. In this context, the asset management plan should be updated as the strategic priorities and capital needs of the Municipality change. This can be accomplished in conjunction with specific legislative requirements (i.e. 5-year review of asset management plan under Infrastructure for Jobs and Prosperity Act), as well as the Municipality's annual budget process. Further integration into other Municipality financial/planning documents would assist in ensuring the ongoing accuracy of the asset management plan, as well as the integrated financial/planning documents.

2 State of Local Infrastructure and Levels of Service

2.1 Introduction

This section provides an analysis of the Municipality's assets, the current service levels provided by those assets, and the service levels the Municipality intends to deliver into the future.

The difficulty in assessing local infrastructure is that it may not be consistent between communities. In larger communities – even at a same class of road using the same Pavement Condition Index or Gravel Condition Index – the expectation is higher and may overstate the quality of rural road networks when compared to more urban areas.

O. Reg. 588/17 requires that for each asset category included in the asset management plan, the following information must be identified:

- Summary of the assets;
- Replacement cost of the assets;
- Average age of the assets (it is noted that the Regulation specifically requires average age to be determined by assessing the age of asset components);
- Information available on condition of assets; and
- Approach to condition assessments (based on recognized and generally accepted good engineering practices where appropriate)

Asset management plans must identify the current levels of service being provided for each asset category. For core municipal infrastructure assets, both the qualitative descriptions pertaining to community levels of service, and metrics pertaining to technical levels of service, are prescribed by O. Reg. 588/17. For all other infrastructure assets, each municipality will need to establish its own measures for levels of service.

Asset management plans must also include a 10-year forecast identifying the proposed levels of service for each asset category. The proposed levels of service will be defined using the qualitative descriptions and technical metrics that the municipality uses to define current levels of service.

The rest of this chapter addresses the requirements identified above, with each section focusing on an individual asset category.

2.2 Roads

2.2.1 State of Local Infrastructure

The Township currently owns and manages 74.10 centreline kilometres of road assets with a 2022 replacement value totaling approximately \$20,016,511. The replacement value has been estimated based on the replacement costs, as identified in the Lifecycle Management Strategy section of this report. The road network consists of a single surface type – gravel and all roads reside in a rural environment. Table 2-1,

and **Error! Reference source not found.** provide a breakdown of the road network by surface type and roadside environment. The entirety of the road network, on average, is 16 years old.

Table 2-1

Roads – Surface Type

| Surface Type | Centreline Kilometres | Age (Weighted Average) | Replacement Costs | |
|--------------|--------------------------|------------------------------|-------------------|---------------|
| Gravel | 74.10 | 16 | \$ | 20,016,511.83 |
| TOTAL | 74.10 | 16 | \$ | 20,016,511.83 |

Figure 2-1

Map – Road Network



2.2.2 Condition

While asset age may provide some limited context to the functional state of an asset, an assessed physical condition is a better measure of where an asset is in its lifecycle. Physical condition therefore provides a more accurate estimate of an asset's remaining service life. The Municipality's Public Works Department undertook a 2022 review of the physical condition rating for each road segment in the network. Updates are included in the plan when major investments have taken place. This physical condition rating is provided on a scale of 0-100, with 100 being a perfect condition and 0 indicating an asset at the end of its service life. To better communicate the condition of the road network, these numeric condition ratings have been segmented into qualitative condition states.

Table 2-2 summarizes the various physical condition ratings and the condition state they represent for road assets.

Table 2-2

Road Condition States Defined with Respect to Physical Condition

| Physical Condition – Beginning | Physical Condition – Ending | Condition State | Condition Definition | Length (Km) |
|-----------------------------------|-----------------------------------|--------------------|--|-------------|
| 1 | 39 | Poor | Widespread signs of deterioration, some assets may be unusable. Service is affected. | 7.3 |
| 40 | 59 | Fair | Some elements exhibit significant deficiencies, Asset requires attention. | 31.6 |
| 60 | 79 | Good | Good condition, few elements exhibit existing deficiencies. | 21.6 |
| 80 | 100 | Very Good | Well maintained, good condition, new or recently rehabilitated. | 13.7 |

Table 2-3

Roads — Illustration of Condition State




Table 2-4 examines the average condition of the road network by surface type. Adjustments to the physical condition are performed based on the lifecycle degradation or set to known values when capital improvements are completed (i.e. rehabilitation or replacement activities being performed). The physical condition ratings utilized in this plan are from 2022 and represent the most up-to date information available to the Municipality at this time.


As illustrated in Table 2-4, our Class 4 roads are in a "Good" condition state and our seasonal roads are in a "Fair" State with a physical condition of 61.

Table 2-4

Road Condition Analysis

| Surface Type | Centreline Kilometres | Physical Condition | Average Condition State |
|--------------|--------------------------|--------------------|-------------------------|
| Gravel | 74.10 | 60.64 | Good |
| TOTAL | 74.10 | 60.64 | Good |

Figure 2-2



2.2.3 Current and Proposed Levels of Service

The levels of service currently provided by the Municipality's road network is, in part, a result of the state of local infrastructure identified above. Road assets have prescribed levels of service reporting requirements under O. Reg. 588/17. These requirements include levels of service reporting from two different levels, i.e. community levels of service and technical levels of service. Community levels of service objectives describe service levels in terms that customers understand and reflect their scope and quality expectations of the road network. Technical levels of service describe the scope and quality of Municipality roads through performance measures that can be quantified, evaluated, and detail how effectively a municipality provides services. Table 2-5 presents the current levels of service measures as mandated by O. Reg. 588/17.

Table 2-5

Road Current Levels of Service – O. Reg. 588/17

| Levels of Service | Service Attribute | Current Levels of Service | Performance |
|--------------------------------|-------------------|--|------------------------|
| Category | | | |
| Community Levels of Service | Scope | Municipal Roads are utilized by passenger vehicles, emergency vehicles, pedestrians, cyclists, farm equipment and heavy transport vehicles. | |
| | Quality | Table 2-2 details how road physical condition is segregated into qualitative condition states. Roads in a poor, or worse, condition state could face possible load restrictions or access issues. | |
| Technical Levels of Service | Scope | Number of lane-kilometres of each of arterial roads, collector roads and local roads as a proportion of square kilometres of land area of the municipality. | 1.34 |
| | Quality | For paved roads in the municipality, the average pavement condition index value. For unpaved roads in the municipality, the average surface condition (e.g. excellent, good, fair or poor). | 1. N/A 2. 61 (Good) |

The scope of our municipality shows local roads as a proportion of square kilometres of land as 1.55 with paved coming in at a PCI of 66 (Good) and unpaved coming in with a GCI of 67 (Good).

As noted earlier, municipal asset management plans must identify both the existing and proposed levels of service for each asset category. Discussions with Municipality staff have formalized the proposed levels of service objectives. These technical levels of service are provided in the form of minimum acceptable levels of service for road assets. These minimum technical levels of service criteria have been designed to indicate the lowest physical condition any road in the Municipality should reach before an intervention or activity is performed to improve the road's condition. Furthermore, the minimum technical levels of service have been stratified into distinct expected levels of service objectives based on the road classifications identified in O. Reg. 239/02: Minimum Maintenance Standards (MMS) for Municipal Highways. O. Reg. 239/02 classifies roads based on their average daily traffic and speed limits and ultimately assigns a numerical score (1 to 6), where a lower number signifies a more heavily travelled road and/or a higher speed limit road. Table 2-6 details the Municipality's proposed technical levels of service, in terms of minimum expected physical condition, for road classifications as defined in O. Reg. 239/02.

The higher proposed levels of service on class 4 roads signals the relatively higher importance of these roads by the Municipality.

Table 2-6
Roads Proposed Levels of Service

| MMS Road Class | Minimum Physical Condition |
|----------------|----------------------------|
| 4 | 80 |
| 5 | 70 |
| 6 | 60 |
| Seasonal | 40 |

The table details what proportion of the road network falls below the proposed technical levels of service objectives, by MMS road classification. The Class 4 gravel roads have 82% who do not meet the proposed level of service and 68% of the Class 6 fail to meet the proposed levels of service. Broken down further, thirty-one road sections currently do not meet their proposed standard including:

- AIDIE CREEK GARDEN ROAD S1
- AIDIE CREEK GARDEN ROAD S3
- ALPINE RD S1
- BEAVER ROAD S1
- BEAVER ROAD S2
- BEAVER ROAD S3
- CHAMBERLAIN ROAD 2 S2
- CHAMBERLAIN ROAD 2 S4
- CHAMBERLAIN ROAD 2 S6
- CHAMBERLAIN ROAD 4 S1
- CHAMBERLAIN ROAD 4 S2

- CHAMBERLAIN ROAD 5 S1
- CHAMBERLAIN ROAD 5 S2
- CHAMBERLAIN ROAD 5 S3
- CHAMBERLAIN ROAD 5 S4
- CHAMBERLAIN ROAD 6 S1
- CHAMBERLAIN ROAD 7 S1
- CHAMBERLAIN ROAD 7 S2
- CHAMBERLAIN ROAD 7 S3
- JACK PINE ROAD S1
- LITTLE ROAD S1
- MARSH ROAD S1
- STONEY LONESOME RD S1
- STONEY LONESOME RD S2
- WAWBEWAWA ROAD S1
- WAWBEWAWA ROAD S3
- WAWBEWAWA ROAD S4
- WAWBEWAWA ROAD S5
- WAWBEWAWA ROAD S6
- WEST RD S2
- WEST ROAD S1

Table 2-7
Roads Proposed Levels of Service

| Road Surface | MMS Road Class | Centreline Kilometres | Proposed Level of Service | Physical Condition (Weighted Average) | Average Condition State | Lowest Level of Service | % of Km's Less than Proposed Level of Service |
|--------------|-------------------|--------------------------|------------------------------|--|-------------------------------|-------------------------------|---|
| | 4 | 64.98 | 80 | 62 | Good | 27 | 82% |
| Gravel | 5 | 0.00 | 70 | N/A | N/A | N/A | N/A |
| Graver | 6 | 8.50 | 60 | 60 | Good | 35 | 68% |
| | Seasonal | 0.62 | 40 | 45 | Fair | 45 | 0% |
| TOTAL | | 74.10 | n/a | 61 | Good | 27 | |

2.3 Bridges and Structural Culverts


2.3.1 State of Local Infrastructure

The Municipality currently owns and manages 1 bridge and 3 major culverts, with a 2022 replacement value totaling approximately \$11,160,451 The replacement value has been estimated based on inflating installation costs from the original purchase price. Table 2-8 provides a summary of count, age, and replacement value for the current bridge and culvert network. The average age of the Municipality's bridges and culverts is just over 40 years, with the bridge averaging 45 years, compared to culverts averaging 40 years.

Table 2-8
Bridge Network –Type

| Туре | Quantity | Age (Weighted Average) | Replacement Cost |
|---------|----------|------------------------------|---------------------|
| Bridge | 4 | 64 | \$ 10,805,889.01 |
| Culvert | 6 | 39 | \$ 2,859,093.13 |
| TOTAL | 10 | 58 | \$ 13,664,982.14 |

Figure 2-3






Figure 2-4

Map- Bridges and Culverts

2.3.2 Condition

The Municipality's OSIM report assessed the condition of the bridge and culvert network, applying a bridge condition index (BCI) for asset. A BCI score is provided on a numeric scale of 0-100, and is a measure of the overall condition of the structure based on an evaluation of individual components. Similar to road assets, to better communicate the condition of the bridge and culvert network, the numeric condition ratings have been segmented into qualitative condition states as summarized

Table 2-9.

Table 2-9

Bridge and Culvert Condition States Defined with Respect to BCI

| Physical Condition - Beginning | Physical Condition – Ending | Condition State | Condition Description | |
|---------------------------------|-----------------------------------|--------------------|--|----------------|
| 0 | 60 | Poor | Widespread signs of deterioration, some assets may be unusable. Service is affected. | \$9,174,874.60 |
| 61 | 75 | Fair | Some elements exhibit significant deficiencies, Asset requires attention. | \$2,973,935.84 |
| 75 | 90 | Good | Good condition, few elements exhibit existing deficiencies. | \$ - |
| 90 | 100 | Very Good | Well maintained, good condition, new or recently rehabilitated. | \$1,516,171.71 |

As summarized in Table 2-10, our bridges are, on average, in a "Poor" condition state, while culverts are in also in a "Poor" condition state. Assessed for the entire bridge and culvert network, all structures provide an average BCI of 39, representing a "Poor" condition state. The lowest observed condition in the bridge network is 38.8 (Poor), and for culverts is 0.8 (Poor). All culverts are in the Poor or Fair condition whereas one bridge is listed as Very Good. The following bridges and culverts are listed in poor and fair condition:


| Condition | Bridges | Culverts |
|-----------|------------------------|----------------------|
| Poor | Aidie Creek | Blackburn Culvert #3 |
| | Krugerdorf Bridge | Blackburn Culvert #4 |
| | | Crocodile Creek #5 |
| | | Crocodile Creek #6 |
| | | West Road #2 |
| Fair | Lyon's Bridge (Road 7) | Crocodile Creek #1 |

Table 2-10

Bridge and Culvert Condition Average

| Туре | Quantity | BCI (Weighted Average) | Minimum Observed BCI | Average Condition State |
|---------|----------|------------------------------|----------------------|-------------------------------|
| Bridge | 1 | 56 | 56 | Poor |
| Culvert | 3 | 53 | 39 | Poor |
| TOTAL | 4 | 53.4 | 39 | Poor |

Figure 2-5



2.3.3 Current Levels of Service

The levels of service currently provided by the Municipality's bridge and culvert network is, in part, a result of the state of local infrastructure identified above. Bridge and culvert assets have prescribed levels of service reporting requirements under O. Reg. 588/17. These requirements include levels of service reporting from two different levels, i.e. community levels of service and technical levels of service. Community levels of service objectives describe service levels in terms that customers understand and reflect their scope and quality expectations of the bridge and culvert network. Technical levels of service describe the scope and quality of Municipality bridges and culverts through performance measures that can be quantified, evaluated, and detail how effectively a municipality provides services.

Table 2-11 presents the current levels of service as mandated by O. Reg. 588/17.

Table 2-11

Bridge and Culvert Current Levels of Service – O. Reg. 588/17

| Levels of Service Category | Service Attribute | Current Levels of Service |
|-----------------------------|-------------------|-----------------------------------|
| Community Levels of Service | Scope | Bridges and Culverts are utilized |
| | | by passenger vehicles, |
| | | emergency vehicles, |
| | | pedestrians, cyclists, farm |
| | | equipment and heavy transport |
| | | vehicles. |
| | Quality | Table 2-9 details how BCI is |
| | | segregated into qualitative |
| | | condition states. Bridges or |
| | | culverts in a poor, or worse, |
| | | condition state could face |
| | | possible load restrictions. |
| Technical Levels of Service | Scope | Krugerdorf Bridge has load |
| | | restrictions which limit traffic. |
| | | |
| | | 10% of the overall network. |
| | Quality | Table 2-10 summarizes the |
| | | average condition of the |
| | | Municipality's bridge and |
| | | culvert network. |

2.3.4 Proposed Levels of Service

As noted earlier, municipal asset management plans must identify both the existing and proposed levels of service for each asset category. The previous subsection described the current levels of service being provided by the Municipality's bridges. This subsection will define the proposed levels of service for these assets.

Discussions with Municipality staff have formalized the proposed levels of service objectives. These technical levels of service are provided in the form of minimum acceptable levels of service for bridge and structural culvert assets. The Municipality has a relatively few number of bridge and structural culverts and is proposing to maintain the existing access. Closures of any of these assets would result in unacceptable and dangerous detouring of emergency vehicles for much of the population. Due to the importance of these assets the municipality strives to maintain the structures as at least a 75 or Good rating. Currently, only one bridge is meeting the desired level of service.

2.4 Road Culverts

2.4.1 State of Local Infrastructure

The Municipality currently owns and maintains 193 culverts with a 2022 replacement value totaling approximately \$319,102. The replacement value has been estimated based on the replacement costs, as gathered from an Inglis Farm Drainage Inc. cost sheet. Assessed across the entire network our culverts have an average age of 21 years.

Table 2-12

Culvert Network – Material Type

| Culvert Type | Quantity | Age (Weighted Average) | Replacement Cost |
|-----------------|----------|---------------------------|---------------------|
| Metal | 184 | | \$299,783 |
| Cement | 2 | | \$10,452 |
| Plastic | 7 | | \$8,867 |
| TOTAL | 193 | 21 | \$319,102 |

Figure 2-6




Table 2-13

Culvert Network - Size

| Culvert Diameter | Quantity | Age (Weighted Average) | Replacement Cost |
|------------------------|----------|---------------------------|---------------------|
| <=375mm (15 inches) | 45 | | \$25,138 |
| 375 mm - 750 mm | 116 | | \$166,480 |
| >750 mm (30 inches) | 32 | | \$127,484 |
| TOTAL | 193 | 21 | \$319,102 |

Figure 2-7





Figure 2-8

Map- Road Culverts



2.4.2 Condition

While asset age may provide some limited context to the functional state of an asset, an assessed physical condition is a better measure of where an asset is in its lifecycle. Physical condition therefore provides a more accurate estimate of an asset's remaining service life. The Public Works Department assessed our Culvert Network in 2016 and as replacements are made. A physical condition rating is provided on a scale of 1-4, with 4 being a perfect condition and 1 indicating an asset at the end of its service life. To better communicate the condition of the culvert network, these numeric condition ratings have been segmented into qualitative condition states.


Table 2-14 summarizes the various physical condition ratings and the condition state they represent for culvert assets. There are 19 culverts in poor condition and 25 culverts in the fair condition.

Table 2-14

Culvert Condition States Defined with Respect to Physical Condition

| Physical Condition | Condition State | Condition Definition | Replacement Value |
|--------------------|--------------------|--|----------------------|
| 1 | Poor | Widespread signs of deterioration, some assets may be unusable. Service is affected. | \$39,490 |
| 2 | Fair | Some elements exhibit significant deficiencies, Asset requires attention. | \$43,782 |
| 3 | Good | Good condition, few elements exhibit existing deficiencies. | \$73,627 |
| 4 | Very Good | Well maintained, good condition, new or recently rehabilitated. | \$162,204 |

Figure 2-9



2.4.3 Current Levels of Service

The levels of service currently provided by the Municipality's road culvert network is, in part, a result of the state of local infrastructure identified above. A levels of service analysis defines the current levels of service and enables the Township to periodically evaluate these service level objectives.

Table 2-15
Culvert Current Levels of Service

| Levels of Service Category | Service Attribute | Current Levels of Service |
|-----------------------------|-------------------|----------------------------------|
| Community Levels of Service | Scope | Culverts are utilized by |
| | | passenger vehicles, emergency |
| | | vehicles, pedestrians, cyclists, |
| | | farm equipment and heavy |
| | | transport vehicles. |
| | Quality | Table 2-12 details our culverts |
| | | in qualitative condition states. |
| | | Culverts in a poor, or worse, |
| | | condition state could face |
| | | possible load restrictions, |
| | | access issues or localized |
| | | flooding. |
| Technical Levels of Service | Scope | Figure 2-9 depicts the |
| | | Municipality's culvert network |
| | | by surface type |
| | Quality | Figure 2-9 summarized the |
| | | average condition of the |
| | | Municipality's culvert network |

2.4.4 Proposed Levels of Service

Discussions with Municipal staff have set out a proposed level of service to replace culverts as they enter the poor condition. If a project is completed on that section of roadway culverts may be replaced in the Fair or Good conditions based on the judgement of staff. Currently, 44 culverts fail to meet the proposed standard. The Municipality is also moving to plastic culverts from metal to help achieve a longer overall life for the assets.

Table 2-16

Number of Culverts by Condition State

| Physical Condition | Condition State | Condition Definition | Number of Culverts |
|--------------------|--------------------|--|-----------------------|
| 1 | Poor | Widespread signs of deterioration, some assets may be unusable. Service is affected. | 19 |
| 2 | Fair | Some elements exhibit significant deficiencies, Asset requires attention. | 25 |
| 3 | Good | Good condition, few elements exhibit existing deficiencies. | 55 |
| 4 | Very Good | Well maintained, good condition, new or recently rehabilitated. | 94 |

2.5 Railway Crossings

2.5.1 State of Local Infrastructure

The Municipality currently has seven railway crossings which travel across its roads. The responsibility for the repairs to these crossings are continuing to be a matter of debate. Often the cost falls onto the Townships instead of the Ontario Northland Rail Network and we have included it within our plan.

Table 2-17
Railway Crossings

| Crossing | Year Round | Seasonal | Detour Available | Арр | proximate Cost | Average Age |
|-------------|------------|----------|------------------|-----|----------------|----------------|
| Road 7 | 0 | 0 | Yes | \$ | 17,000.00 | 1906 |
| Aidie Creek | 1 | 1 | No | \$ | 17,000.00 | 1906 |
| Road 5 | 0 | 1 | No | \$ | 17,000.00 | 1906 |
| Road 4 | 5 | 1 | Yes | \$ | 17,000.00 | 1906 |
| Road 3 | 3 | 1 | Yes | \$ | 17,000.00 | 1906 |
| Road 2 | 0 | 0 | Yes | \$ | 17,000.00 | 1906 |
| Alpine Road | 1 | 0 | No | \$ | 17,000.00 | 1906 |

2.5.2 Condition

The Municipality has used a four point scale as listed below to rate the condition of the crossings. The Crossings have been given a useful life of 100 years with anything over 140% listed as poor. This expected life has been estimated based on internet research. The Municipality currently only has the age of its railway crossings to inform condition.

Table 2-18

Culvert Condition States Defined with Respect to Physical Condition

| UL% | Condition State | Replacement Value |
|------------------|--------------------|-------------------|
| 140% ≤ UL% | Poor | \$0 |
| 90% ≤ UL% < 140% | Fair | \$119,000 |
| 45% ≤ UL% < 90% | Good | \$0 |
| UL% < 45% | Very Good | \$0 |

Figure 2-10

The railway tracks went in at the same time in 1906. This gives all the crossings the same again. All crossings are in the "Fair" category.

| Crossing | Year Round | Seasonal | Detour Available | Ар | proximate Cost | Average Age | Useful Life | Condition |
|-------------|------------|----------|------------------|----|----------------|----------------|-------------|-----------|
| Road 7 | 0 | 0 | Yes | \$ | 17,000.00 | 1906 | 116% | Fair |
| Aidie Creek | 1 | 1 | No | \$ | 17,000.00 | 1906 | 116% | Fair |
| Road 5 | 0 | 1 | No | \$ | 17,000.00 | 1906 | 116% | Fair |
| Road 4 | 5 | 1 | Yes | \$ | 17,000.00 | 1906 | 116% | Fair |
| Road 3 | 3 | 1 | Yes | \$ | 17,000.00 | 1906 | 116% | Fair |
| Road 2 | 0 | 0 | Yes | \$ | 17,000.00 | 1906 | 116% | Fair |
| Alpine Road | 1 | 0 | No | \$ | 17,000.00 | 1906 | 116% | Fair |

2.5.3 Current Levels of Service

The levels of service currently provided by the Municipality's railway crossings is, in part, a result of the state of local infrastructure identified above. A levels of service analysis defines the current levels of service and enables the Township to periodically evaluate these service level objectives.

Table 2.5
Culvert Current Levels of Service

| Levels of Service Category | Service Attribute | Current Levels of Service | | |
|-----------------------------|-------------------|-----------------------------------|--|--|
| Community Levels of Service | Scope | Railway Crossings are utilized by | | |
| | | passenger vehicles, emergency | | |
| | | vehicles, pedestrians, cyclists, | | |
| | | farm equipment and heavy | | |
| | | transport vehicles. | | |
| | Quality | The table above details our | | |
| | | crossings in qualitative | | |
| | | condition states. Crossings in a | | |
| | | poor, or worse, condition state | | |
| | | could face possible load | | |
| | | restrictions, or access issues. | | |
| Technical Levels of Service | Scope | The table above depicts the | | |
| | | Municipality's crossing network | | |
| | Quality | The Table above summarizes | | |
| | | the average condition of the | | |
| | | Municipality's culvert network | | |


2.5.4 Proposed Levels of Service

With the aging assets all at the same time the risk is that they could fail quickly one after another. The railway crossings in some cases are the sole access for a resident to their home, farm, or property. In other cases, the detours are so long that they may effectively cut off service to properties for emergency services. The municipality is proposing to maintain all existing crossings but with the large costs some with detours may be done over the longer term to spread out the costs. Others with no detours will need an immediate fix.

| Crossing | Year Round | Seasonal | Detour Available | Proposed Service |
|-------------|------------|----------|------------------|------------------|
| Road 7 | 0 | 0 | Yes | Multi-year |
| Aidie Creek | 1 | 1 | No | Immediate |
| Road 5 | 0 | 1 | No | Immediate |
| Road 4 | 5 | 1 | Yes | Multi-year |
| Road 3 | 3 | 1 | Yes | Multi-year |
| Road 2 | 0 | 0 | Yes | Multi-year |
| Alpine Road | 1 | 0 | No | Immediate |

Figure 2-11
Crossings with no Detour


Aidie Creek



Road 5



Alpine Road



2.6 Facilities

2.6.1 State of Local Infrastructure

The Municipality currently owns and manages 5 buildings, and one park, with a 2022 replacement value totaling approximately \$577,764. Facilities assets range in cost with a breakdown of facility asset numbers and replacement costs by category provided in Table 2-19. Please note that for larger facilities the structure itself has not been included in the replacement costs.

Table 2-19

Facility – Average Age and Replacement Cost

| Facility | Age (Weighted Average) | Re | eplacement Cost |
|----------------------|------------------------------|----|--------------------|
| Community Hall | 29 | \$ | 138,737.24 |
| Municipal Shop (New) | 13 | \$ | 78,500.00 |
| Municipal Shop (Old) | 62 | \$ | 154,130.16 |
| Sand/Salt Shed | 39 | \$ | 88,754.54 |
| Ballfield and Park | 12 | \$ | 114,582.46 |
| Waste Site | 1 | \$ | 3,060.00 |
| TOTAL | 41 | \$ | 577,764.39 |

2.6.2 Condition

The Municipality broke down the facilities into their individual assets to assess their condition. To make it easier to interpret conditions a four point scale as show in

| Table 2-20 was used. Useful Life was broken down to exceed 100% to reflect that many assets may still be usable beyond their expected life and will be maintained until replacement makes sense. |
|--|
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |

Table 2-20
Facilities – Condition States

| UL% | Condition | Condition | Replacement |
|------------------|-----------|------------------|-------------|
| UL% | State | Definition | Value |
| | | Widespread | |
| | | signs of | |
| | | deterioration, | |
| | Poor | some assets | |
| | P001 | may be | |
| | | unusable. | |
| | | Service is | |
| 140% ≤ UL% | | affected. | \$121,525 |
| | | Some elements | |
| | | exhibit | |
| | Fair | significant | |
| | Fall | deficiencies, | |
| | | Asset requires | |
| 90% ≤ UL% < 140% | | attention. | \$216,789 |
| | | Good condition, | |
| | Good | few elements | |
| | Good | exhibit existing | |
| 45% ≤ UL% < 90% | | deficiencies. | \$117,692 |
| | | Well | |
| | | maintained, | |
| | Very Good | good condition, | |
| | | new or recently | |
| UL% < 45% | | rehabilitated. | \$121,758 |

2.6.3 Current Levels of Service

In terms of service, facilities require a more detailed analysis than other assets as they are more complex. Furthermore, there is no single dimension to evaluate performance. Some issues may be an immediate safety concern while others may be cosmetic. We currently have one facilities in poor condition – the Sand/Salt Shed.

Table 2-21
Facilities – Average Condition State

| Facility | % Life Used (Weighted Average) | Average Condition State | Annual Lifecycle Costs |
|----------------------|--------------------------------------|-------------------------------|---------------------------|
| Community Hall | 110% | Fair | \$ 96,222.82 |
| Municipal Shop (New) | 56% | Good | \$ 10,921.57 |
| Municipal Shop (Old) | 124% | Fair | \$ 154,130.16 |
| Sand/Salt Shed | 156% | Poor | \$ 88,754.54 |
| Ballfield and Park | 46% | Good | \$ 17,882.50 |
| Waste Site | 10% | Very Good | \$ 340.00 |
| TOTAL | 100% | Fair | \$ 368,251.59 |

While there are few poor facilities there are assets in poor or fair condition. Broken down further the following assets are in Fair or Poor condition across the facilities:

| Facility | Fair | Poor | Replacement Cost | |
|-------------------------|---|--|---------------------|--|
| Community Hall | Windows Office Floors Refrigerator Stove Furnace x 2 Sinks and Toilets Septic System Radios | Interior Painting Hall Floors Ceiling Fans Hot Water Tank Eavestroughts Desks and Counters Signage | \$91,929 | |
| Municipal Shop (New) | Hot Water Tank Signage | Interior Painting | \$3,500 | |
| Municipal Shop (Old) | Structure | None | \$154,130 | |
| Sand/Salt Shed | None | Structure | \$88,754 | |
| Ballfield and Park | None | None | \$0.00 | |
| Waste Site | None | None | \$0.00 | |
| TOTAL | 11 | | \$ 338,313 | |

2.6.4 Proposed Levels of Service

The Municipality is beginning with the items in poor condition and attempting to work with funding programs to target locations when possible. This is especially true in the recreational parks where

traditionally more funding programs are available. The Municipality is proposing to maintain their existing level of service where possible. If an item is considered unsafe such as playground equipment or a park shelter it will be removed or restricted until a suitable replacement can be funded. The Municipality has a goal of continuing to make its facilities fully accessible and investments in the facilities will work toward this goal.

2.7 Vehicles and Equipment

2.7.1 State of Local Infrastructure

The Municipality currently owns and manages 4 vehicles and 8 pieces of equipment, with a 2022 replacement value totaling approximately \$997,268. This value represents a Shared Service Agreement with the Municipality of Charlton and Dack and shared equipment is only recorded at 50%. Please note that this does not include the Englehart and Area Fire Department equipment which is tracked separately. The replacement value has been based on inflating historical cost. Table 2-22 provides a summary of quantity, expected useful life, age, and replacement value of Municipality equipment assets. The average age of Unshared vehicles is 8 years and of Shared Vehicles is 12 years. The average age of Unshared equipment is 14 years and of Shared equipment is 7 years. Overall, the municipality has vehicles and equipment with an average age of 9 years.

Table 2-22
Equipment Infrastructure Summary

| Туре | Agreement Type | # of Pieces | % Life Used (Weighted Average) | Age (Weighted Average) | Re | eplacement Cost | Highest % Used | Average Condition State |
|-----------|-------------------|-------------|--------------------------------------|------------------------------|----|--------------------|-------------------|-------------------------------|
| Vehicle | Unshared | 2 | 34% | 8 | \$ | 166,195.70 | 36% | Very Good |
| venicie | Shared | 2 | 69% | 12 | \$ | 44,927.88 | 85% | Good |
| Fauinment | Unshared | 2 | 13% | 14 | \$ | 619,210.66 | 16% | Very Good |
| Equipment | Shared | 6 | 11% | 7 | \$ | 166,934.73 | 51% | Very Good |
| TOTAL | | 12 | | 9 | \$ | 997,268.96 | 85% | Very Good |

Figure 2-12





Figure 2-13



2.7.2 Condition


The Municipality currently only has the age of its fleet to inform condition. We have used a four class condition state to with expected useful life that could exceed 100%. As presented, the average age of our fleet is 8 years, or a "Very Good" condition state. The next Unshared Vehicle up for replacement is the 2018 Chevrolet Pickup truck due for replacement in 2028 with a 2022 value of \$48,075. The next Shared Vehicle up for replacement is the 2007 International Plow Truck due for replacement in 2025 with an estimated 2022 cost of \$48,027 (Chamberlain responsible for 50%). The next Unshared Equipment up for replacement is the 1996 Backhoe due for replacement in 2027 at an estimated 2022 cost of \$123,356. The next Shared Equipment up for replacement is the 2015 trailer due for replacement in 2028 at an estimated value of \$13,439.

Table 2-23

Vehicles and Equipment – Condition State

| UL% | Condition State | Replacement Value | |
|------------------|--------------------|----------------------|--|
| 140% ≤ UL% | Poor | \$0 | |
| 90% ≤ UL% < 140% | Fair | \$0 | |
| 45% ≤ UL% < 90% | Good | \$179,339 | |
| UL% < 45% | Very Good | \$817,930 | |

Figure 2-14



2.7.3 Current Levels of Service

| Levels of Service Category | Service Attribute | Current Levels of Service |
|-----------------------------|-------------------|---|
| Community Levels of Service | Scope | Vehicles and equipment are utilized to maintain our road network to ensure they are passable by passenger vehicles, emergency vehicles, pedestrians, cyclists, farm equipment and heavy transport vehicles. |
| | Quality | Vehicles and equipment in a poor, or worse, condition state could cause the municipality to meet its minimum maintenance standards. |
| Technical Levels of Service | Scope | The table above depicts the Municipality's vehicle and equipment. |
| | Quality | The table above depicts the Table 2-22 summarized the average condition of the Municipality's vehicles and equipment. |

2.7.4

2.7.5 Proposed Levels of Service

The Municipality has a Shared Services Agreement with the Township of Chamberlain and strive to manage their vehicle and equipment networks to share equipment where it makes sense and to manage their own equipment where it makes sense. A joint Public Works Committee makes recommendation to Council on any additions to the base set of equipment. The Municipalities have outlined the goal of maintaining the following equipment at a minimum:

Unshared Equipment:

- One Pickup Truck
- One Plow Truck
- One Grader
- One Backhoe

Shared Equipment:

- One Plow Truck
- One Pickup Truck
- One Brush Mower
- Two Trailers
- One Excavator

The Municipalities intend to replace vehicles near their expected useful life. This means that is reasonable to expect that only a relatively small number of vehicles will have a Useful Life percentage greater than 100%. Currently, no equipment exceed 100% of its expected life.

2.8 Signs

2.8.1 State of Local Infrastructure

The Municipality currently owns and manages 53 signs with a 2022 replacement value totaling approximately \$2650. The replacement value has been estimated based on the replacement costs by researching on Owl Signs Website. The signs have an average age of 21 years and a replacement cost of \$2650.

Table 2-24
Signs – Average Age and Replacement Costs

| Sign Type | Quantity | Average Condition | Minimum Condition | Average Condition State | % Reflective | Rep | lacement Cost |
|----------------------------------|----------|----------------------|----------------------|-------------------------------|--------------|-----|------------------|
| Children at Play | 3 | 2.00 | 1.00 | Fair | 33% | \$ | 150.00 |
| Danger | 2 | 2.00 | 1.00 | Fair | 50% | \$ | 100.00 |
| General Information | 0 | N/A | N/A | N/A | N/A | \$ | = |
| Horse and Buggy | 1 | 3.00 | 3.00 | Good | 0% | \$ | 50.00 |
| Intersection | 1 | 3.00 | 3.00 | Good | 100% | \$ | 50.00 |
| Municipality Welcome | 0 | N/A | N/A | N/A | N/A | \$ | - |
| No Exit | 6 | 2.67 | 2.00 | Fair | 83% | \$ | 300.00 |
| No Snowmobiling | 0 | N/A | N/A | N/A | N/A | \$ | - |
| No Trespassing | 0 | N/A | N/A | N/A | N/A | \$ | - |
| Railroad Crossing | 0 | N/A | N/A | N/A | N/A | \$ | - |
| Recreation and Cultural Interest | 0 | N/A | N/A | N/A | N/A | \$ | - |
| Route Marker | 0 | N/A | N/A | N/A | N/A | \$ | - |
| School Bus Stop Ahead | 0 | N/A | N/A | N/A | N/A | \$ | - |
| Seasonal Road | 1 | 2.00 | 2.00 | Fair | 0% | \$ | 50.00 |
| Speed Regulation | 2 | 3.00 | 3.00 | Good | 100% | \$ | 100.00 |
| Stop | 37 | 2.46 | 1.00 | Fair | 86% | \$ | 1,850.00 |
| Street Sign | 0 | N/A | N/A | N/A | N/A | \$ | - |
| Turn and Curve | 0 | N/A | N/A | N/A | N/A | \$ | -] |
| Yield | 0 | N/A | N/A | N/A | N/A | \$ | - |
| TOTAL | 53 | | | Poor | 81% | \$ | 2,650.00 |

2.8.2 Condition

While asset age may provide some limited context to the functional state of an asset, an assessed physical condition is a better measure of where an asset is in its lifecycle. Physical condition therefore provides a more accurate estimate of an asset's remaining service life. The Public Works Department assessed our Sign Network in 2022, as replacements are made and when projects are undertaken on

that section of road. A physical condition rating is provided on a scale of 0-4, with 4 being a perfect condition and 0 indicating an asset at the end of its service life. To better communicate the condition of the sign network, these numeric condition ratings have been segmented into qualitative condition states. The table below summarizes the various physical condition ratings and the condition state they represent for sign assets.

Table 2-25
Signs-Condition Rating

| Physical Condition | Condition State | Quantity | Replacement Value |
|--------------------|-----------------|----------|----------------------|
| 1 | Poor | 19 | \$950 |
| 2 | Fair | 0 | \$0 |
| 3 | Good | 34 | \$1,700 |
| 4 | Very Good | 0 | \$0 |

2.8.3 Current Levels of Service

The Municipality currently has 19 signs in the poor condition and no signs in the fair condition for a total of \$7,500. These signs vary across the municipality and have been grouped into sign types for simplicity. The municipality has a achieved an overall 81% reflectivity rate with a low of 0% to a high of 100%.

2.8.4 Proposed Levels of Service

The municipality has an ultimate goal of moving signs to be fully reflective to improve visibility and safety. The municipality will work on first upgrading poor non reflective signs and progressively moving up the condition state to achieve 100% reflectivity.

3 Lifecycle Management Strategy

3.1 Introduction

This chapter details the lifecycle management strategies required to maintain the current and proposed levels of service presented in Chapter 2. A lifecycle management strategy identifies the recommended lifecycle activities required to achieve the levels of service discussed in the previous chapter. Lifecycle activities are the specified actions that can be performed on assets in order to increase service level and extend service life. These actions can be carried out on a planned schedule in a prescriptive manner, or through a reactionary approach where the treatments are only carried out when specified conditions are met. O. Reg. 588/17 requires that all potential lifecycle activity options be presented, with the aim of analyzing these options in search of identifying the set of lifecycle activities that can be undertaken at the lowest cost to maintain current levels of service or to provide proposed levels of service. Asset management plans must include a 10-year capital plan that forecasts the lifecycle activities resulting from the lifecycle management strategy. What follows are the lifecycle management strategies for all asset classes contained within this asset management plan, with each section focusing on an individual asset category. Although a considerable amount of effort has been spent on developing lifecycle management strategies informed by observed asset conditions, there are still some assets for which the lifecycle management strategy is age-based. The lifecycle management strategy for these age-based assets is presented in the last section of this chapter. The expenditure forecasts resulting from the lifecycle management strategies for each asset category are also included in the following sections, and have been developed for a 20-year forecast period.

3.2 Roads

3.2.1 Lifecycle Activities

This section will detail the lifecycle activities as documented through discussions with Municipality staff. The lifecycle activities that the Municipality currently employs in the management of its roads include:

- Maintenance Minor Regravelling
- Gravel Top Up (75 mm)
- Gravel Resurfacing (150mm, Brushing, Light Ditching)
- Gravel Rehabilitation (150mm A, 300mm B, Excavation, Brushing, Ditching)
- Gravel Reconstruction (150mm A, 300mm B, Excavation, Brushing, Ditching, Culverts)

Table 3-1 details the costs associated with undertaking these lifecycle activities. The costs are presented on a \$/m basis. These costs are based on unit costs derived from recent contract tenders and discussion with municipal staff.

Table 3-1

Road Treatment Costs by Surface Type

| Lifestyle Activity | | Cost / m |
|-----------------------------------|----|----------|
| Gravel Top Up | \$ | 15.02 |
| (75 mm) | ې | 15.02 |
| Gravel Resurfacing | خ | 38.74 |
| (150mm, Brushing, Light Ditching) | \$ | 30.74 |
| Gravel Rehabilitation | | |
| (150mm A, 300mm B, Excavation, | \$ | 273.11 |
| Brushing, Ditching) | | |
| Gravel Reconstruction | | |
| (150mm A, 300mm B, Excavation, | \$ | 293.11 |
| Brushing, Ditching, Culverts) | | |

3.2.2 Degradation Profiles

Assets deteriorate over time, eventually reaching a point where they have no remaining service life left. However, the path each asset takes in reaching its end of life differs, even for assets of the same type. A condition rating identifies where along the path any particular asset lays, or in other words, how long an asset has left before it reaches its end of life. The municipality works to keep its road network above a condition rating of Good through the use of Top Ups and Resurfacing. If the road network falls into the fair or poor category additional expenses need to be done to reconstruct or rehabilitate the road. There is a limit to Rehabilitation will need to be done approximately every 40 years but when adequate upkeep the municipality believes Reconstruction of the asset could be avoided.

3.2.3 Expected Lifecycle


Combining the treatments and degradation profiles, results in a complete lifecycle management strategy. For surface treated roads it is important to complete the final application to extend the life of the road to its maximum length and reduces long term costs. The difference between Class 4 and the other road types reflect the increased traffic that occurs on these roads.

| Surface Type | Year | Lifecycle Activity |
|-----------------------------------|------|--------------------|
| Class 4 Gravel Roads | 5 | Top Up |
| Class 5, 6, Seasonal Gravel Roads | 7 | Top Up |

3.2.4 Capital Costs / Forecast

Figure 3-1 presents the 20-year expenditure forecast that results from following the lifecycle management strategy detailed above. This forecast illustrates the annual expenditures without any consideration to budgetary constraints. Over the 20-year forecast period, the average annual expenditures would be approximately \$669,607, in 2022 dollars. It is noted that the large expenditure amount shown in year one of the forecast represents the cost of bringing all road segments to their minimum levels of service thresholds.

Figure 3-1
Lifestyle Cycle for Roads



3.3 Bridges and Structural Culverts

3.3.1 Lifecycle Activities

This section will detail the lifecycle activities (capital treatments) as set forth in the 2020 OSIM report and through discussions with Municipality staff. The treatments that the Municipality currently employs in the management of its bridges and culverts include:

- Minor Rehabilitation
- Major rehabilitation
- Reconstruction

Table 3-2 details the costs for the lifecycle activities listed above. These costs are presented as a percentage of estimated replacement cost for the entire bridge, which are derived from averages present in the 2020 OSIM report.

Table 3-2

Bridge and Culvert Treatment Costs as Percent of Total Replacement

| Structure Type | Structure Name | BCI | Last Year | Category | Average Lifespan | Remaining Life | Estimated Current Year Costs | Required Rehabilitation in next 10 years per OSIM | |
|----------------|------------------------|------|-----------|-----------|---------------------|-------------------|---------------------------------|--|------|
| Bridge | Aidie Creek | 56.4 | 1987 | Poor | 75 | 40 | \$ 845,469.55 | \$1,800,000.00 | 213% |
| Bridge | Bailey Bridge (Road 5) | 98.5 | 2018 | Very Good | 75 | 71 | \$ 1,516,171.71 | \$ - | 0% |
| Bridge | Lyon's Bridge (Road 7) | 64.1 | 1991 | Fair | 75 | 44 | \$ 2,057,778.02 | \$1,300,000.00 | 63% |
| Bridge | Krugerdorf Bridge | 38.8 | 1930 | Poor | 75 | -17 | \$ 6,386,469.74 | \$2,390,000.00 | 37% |
| Culvert | Blackburn Culvert #3 | 0.8 | 1991 | Poor | 50 | 19 | \$ 273,964.53 | \$1,000,000.00 | 365% |
| Culvert | Blackburn Culvert #4 | 33.3 | 1990 | Poor | 50 | 18 | \$ 274,268.93 | \$ 320,000.00 | 117% |
| Culvert | Crocodile Creek #1 | 63 | 1995 | Fair | 50 | 23 | \$ 453,300.52 | \$ 150,000.00 | 33% |
| Culvert | Crocodile Creek #5 | 34.3 | 1978 | Poor | 50 | 6 | \$ 714,201.51 | \$ 5,000.00 | 1% |
| Culvert | Crocodile Creek #6 | 53.4 | 1975 | Poor | 50 | 3 | \$ 680,500.34 | \$ 320,000.00 | 47% |
| Culvert | West Road #2 | 60.7 | 1982 | Poor | 50 | 10 | \$ 462,857.31 | \$ 150,000.00 | 32% |

3.3.2 Degradation Profiles

Assets deteriorate over time, eventually reaching a point where they have no remaining service life left. However, the path each asset takes in reaching its end of life differs, even for assets of the same type. A condition rating identifies where along the path any particular asset lays, or in other words, how long an asset has left before it reaches its end of life. These bridges and culverts are regularly assessed by professional engineers and their degradation profiles can be more accurately tracked.

3.3.3 Decision Criteria

Figure 3-2 presents the decision criteria—developed through discussions with Municipality staff—for triggering specific bridge and culvert treatments. When all of the decision criteria for a given asset are met, the corresponding treatment is eligible to be applied. When a treatment is applied, the BCI of the asset is improved by the amount specified in the "Gain to Condition" column, but not to exceed 100.

Figure 3-2
Bridge and Culvert Treatment Decision Criteria

| Physical Condition – Beginning | Physical Condition – Ending | Condition State | Condition Description | Lifecycle Activity | Gain to Condition |
|--------------------------------------|-----------------------------------|--------------------|---|----------------------|----------------------|
| 0 | 60 | Poor | Widespread signs of deterioration, some assets | Reconstruction | |
| | 00 | 1 001 | may be unusable. Service is affected. | Reconstruction | 100 |
| 61 | 75 | Fair | Some elements exhibit significant deficiencies, Asset requires attention. | Major Rehabilitation | 25 |
| 75 | 90 | Good | Good condition, few elements exhibit existing deficiencies. | Minor Rehabilitation | 15 |
| 90 | 100 | Very Good | Well maintained, good condition, new or recently rehabilitated. | Maintenance | 0 |

3.3.4 Expected Life

Combining the treatments, degradation profiles, and decision criteria presented herein results in a complete lifecycle management strategy. The lifecycle strategy as defined for bridges is a preservation strategy, which means that an asset will only receive rehabilitation treatments and not be reconstructed, assuming that the window of opportunity to conduct the rehabilitation treatments has not passed. In other words, as long as budgetary constraints never prevent a bridge rehabilitation from occurring as it becomes due, a bridge will never degrade to a point that it needs to be reconstructed. For example, a representative bridge will degrade from some BCI greater than 75, and upon reaching a BCI of 75, the bridge will be triggered for a rehabilitation, which in turn increases its BCI to 100. This process will loop ad infinitum until such a time as budgetary pressures prevent the rehabilitation from occurring. If the fiscal limits prevent the bridge from being treated for some time period that the bridge's BCI falls to 60 or below, only then will a reconstruction be triggered. Unfortunately, two of our culverts have already crossed the reconstruction threshold.

The lifecycle strategy for culverts is to reconstruct (replace) when the designated BCI is reached. While this strategy is simple—and may not appear to be significantly different from an age-based replacement

strategy—because it is informed by the assessed condition this strategy results in more accurate forecasting. As the asset's condition is regularly re-assessed over time, the timing of the eventual reconstruction could vary significantly from an age-based approach. For example, if the environment that the culvert resides in causes it to degrade quicker or slower than the expected average, and the assessed condition rating reflects this, then the eventual replacement will be triggered at a different time than an age-based approach.


Figure 3-10

Lifecycle Strategy – Culverts

3.3.5 Capital Costs / Forecast

This is the forecast without and budgetary constraints. It includes the complete reconstruction of nine of the structural culverts and bridges as they fall in the fair or poor category. This creates an average annual investment of \$1,214,881 over the next 10 years.





3.4 Facilities

3.4.1 Lifecycle Activities

This section will detail the capital treatments as developed through discussions with Municipality staff. The treatments that the Municipality currently employs in the management of its facilities consists of the replacement of the high-level facility components. This strategy, as it applies to buildings, is intended to replace the common high-level components of a building that deteriorate over time. It is assumed that by replacing these components over time, and through continual maintenance activities of the buildings as a whole, the overall condition of a building will remain in good health. This implies that the core structural and sub-structural components of a building will not degrade appreciably. Therefore, the entire reconstruction of a building has not been modeled within this plan. If circumstances arise that a reconstruction were deemed necessary, then the outputs of this strategy would need to be modified in light of these changes. As some examples, a building's capacity could be deemed to be insufficient for current Municipality needs or some event could harm the structural or sub-structural elements of a building, both of which could necessitate the reconstruction of a building. In such cases, the existing capital plans for these buildings would need to be readdressed through an update to this asset management plan.

3.4.2 Degradation Profile

Assets deteriorate over time, eventually reaching a point where they have no remaining service life left. The municipality, in discussions with staff, have determined that most assets are either maintained or in need of replacement. There is limited opportunities to extend the life but many assets due exceed their average lifespan.


| UL% | Condition State | Condition Definition | Lifecycle |
|------------------|-----------------|-----------------------------|-------------|
| 140% ≤ UL% | Poor | Widespread signs of | |
| | | deterioration, some assets | Replacement |
| | | may be unusable. Service | Neplacement |
| | | is affected. | |
| | | Some elements exhibit | |
| 90% ≤ UL% < 140% | Fair | significant deficiencies, | Replacement |
| | | Asset requires attention. | |
| | | Good condition, few | |
| 45% ≤ UL% < 90% | Good | elements exhibit existing | Maintenance |
| | | deficiencies. | |
| UL% < 45% | Very Good | Well maintained, good | |
| | | condition, new or recently | Maintenance |
| | | rehabilitated. | |

3.4.3 Expected Lifecycle

The municipality is expecting that there is a backlog which creates a large current year estimate. Once this amount is completed the average annual investment is expected to even out.

Figure 3-4

Culvert Replacement Activity



3.4.4 Capital Costs/Forecasts

The Municipality is expecting that the average annual 10 year investment would be \$38,442 for a total 10 year investment of \$368,251. This would address items in the poor and fair categories across the facilities.

3.5 Road Culverts

3.5.1 Lifecycle Activities

This section will detail the capital treatments as developed through discussions with Municipality staff. The staff try to inspect culverts regularly and replace as needed. Culverts are not rehabilitated and are replaced when the asset reaches the end of life.

3.5.2 Degradation Profile

Assets deteriorate over time, eventually reaching a point where they have no remaining service life left. The municipality, in discussions with staff, have determined that most assets are either maintained or in need of replacement. When culverts reach either the poor or fair state they are flagged as needing to be replaced and based on budget and time constraints are completed. Generally, culverts are expected to have a life of 30 years.

3.5.3 Expected Lifecycle

Culvert Network Replacement

The Municipality continues to invest in its culvert network and as shown below is expecting an uneven

replacement cycle which peaks in 2030 with a large investment. Figure 3-5

\$350,000.00 \$300,000.00 \$250,000.00 \$200,000.00 \$150,000.00 \$100,000.00 \$50,000.00 Ś-2022 2023 2024 2030 2025 2026 2027 2028 2029 2031

3.5.4 Capital Costs/Forecasts

The Municipality is expecting that the average annual 10 year investment would be \$30,988 for a total 10 year investment of \$309,881. This would address items in the poor and fair categories across the culverts.

3.6 Signs

3.6.1 Lifecycle Activities

This section will detail the capital treatments as developed through discussions with Municipality staff. The staff try to inspect signs for condition and reflectivity. The plan is to replace signs to improve reflectivity and ensure the quality of the sign is readable to the public. There is not rehabilitation expected for signs just replacement.

3.6.2 Degradation Profile

Assets deteriorate over time, eventually reaching a point where they have no remaining service life left. The municipality, in discussions with staff, have determined that most assets are replaced. Signs require very little maintenance but after outdoor elements are replaced over time.

3.6.3 Expected Lifecycle

The municipalities expect the signs would have a life of 25 years and would be replaced only if conditions require it. Signs may be replaced early for reflectivity if budget allows for it.

3.6.4 Capital Costs/Forecasts

The Municipality expects that an average annual investment of \$265 would be required over the next 10 years for a total of \$2650 over the ten years to address the Poor and Fair signs.

3.7 Age Based Assets

The remainder of the Municipality's assets do not presently have an assessed condition, and as such will all be subject to the same age-based lifecycle management strategy. The following subsections will apply to the following asset classes:

- Vehicles and Equipment;
- Railway Crossings.

3.7.1 Lifecycle Activities

3.7.2 Degradation Profiles

For age based assets, a decreasing degradation profile simply details what percentage of service life is left in light of an expected useful life.

3.7.3 Decision Criteria

For age-based assets, when an asset reaches the end of its service life a replacement treatment is triggered, resulting in the reconstruction or acquisition of a new asset.

3.7.4 Expected Lifecycle


Combining the treatments, degradation profiles, and decision criteria presented herein results in a complete lifecycle management strategy.

3.7.5 Capital Costs / Forecasts

3.7.5.1 Vehicles and Equipment

The vehicles and equipment need an average annual investment of \$22,573 over 10 years to ensure we are replacing vehicles and equipment with like equipment at the end of the term. Most of the equipment was purchased used which could significantly impact expectations if adequate used equipment is not available.





3.8 Population

Based on the most recent census the municipality has a population of 332 an increase of 4.6% from 2011. Overall, the municipality is not expecting that population growth will have an impact on increasing servicing in the future. The greater risk is a shrinking population as has been happening in Northern Ontario and the increasing reliance this puts on the remaining taxpayers. The small population already makes the municipality reliant on Provincial and Federal funding to maintain its assets.

4 Financing Strategy

4.1 Introduction

This chapter details the financing strategy that would sustainably fund the lifecycle management strategies presented previously. This financing strategy focuses on examining how the Municipality can fund the lifecycle activities required to maintain its assets at the current and/or proposed levels of service. The strategy presented is a suggested approach which should be examined and re-evaluated during the annual budgeting processes to ensure the sustainability of the Municipality's financial position as it relates to its assets. O. Reg. 588/17 requires a 10-year capital plan that forecasts the costs of implementing the lifecycle management strategy and the lifecycle activities required therein. To help plan better longer term the municipality has reviewed a capital plan over the next 20 years. The financing strategy forecast (including both expenditure and revenue sources) was prepared consistent with the Municipality's departmental budget structure so that it can be used in conjunction with the annual budget process. Various financing options, including reserve funds, debt, and grants were considered and discussed during the process. The recommended financing strategy identifies rehabilitation and replacement activities required over the forecast period, as described in preceding sections of this plan.

4.2 Annual Costs

The table presents the capital expenditure forecast for each asset class over the 2022- 2041 forecast period. This expenditure forecast is based on the lifecycle activities identified in preceding sections of this plan. It is noted that in the early years of the forecast, certain assets may fall below their respective level of service targets, as the Municipality gradually increases available capital funding. The capital expenditures are in 2022 dollars and are not adjusted for inflation. The greatest immediate shortfall is in the road category where the municipality will not be able to meet its service levels. A small and shrinking population put the existing assets at risk. This plan focuses on only replacement of existing structures with no plans to expand.

Figure 4-1
Annual Capital Investment Required




Table 4-1
2022 Capital Investment Needs

| Expense | 2022 |
|---|------------------|
| Roads | \$ 10,705,507.48 |
| Bridges and Structural Culverts | \$ 12,148,810.44 |
| Road Culverts | \$ - |
| Facilities (buildings, parts, and cemeteries) | \$ 338,313.94 |
| Signs | \$ - |
| Vehicles and Equipment | \$ - |
| | |
| Total | \$ 23,192,631.86 |

To address the immediate capital needs of the municipality would require \$23,192,631 in 2022 with roads and bridges containing the largest dollar amounts.

Figure 4-2

Average Annual Capital Investment Needed




Table 4-2
Average Annual Capital Investment Needs

| Expense | | Annual | | |
|---|----|--------------|--|--|
| Roads | \$ | 673,090.80 | | |
| Bridges and Structural Culverts | \$ | 607,440.52 | | |
| Road Culverts | \$ | 15,494.09 | | |
| Facilities (buildings, parts, and cemeteries) | | 24,553.30 | | |
| Signs | | 132.50 | | |
| Vehicles and Equipment | | 36,079.33 | | |
| Total Tax Supported | | 1,356,790.53 | | |

To better address the long term needs of the municipality, an average annual investment of \$1,356,790.53 is needed for tax supported items annually over the next 20 years.

4.3 Funding Shortfall

Reserves

The Reserve position at December 31, 2020 was \$452,317, representing \$2741 per household. The reserve position does include \$16,749 which has been set aside for the Englehart and Area Fire Department (not included in this plan). It is difficult to determine what would be considered an adequate reserve level.

| | 2020 |
|---------------------------------------|---------------|
| Reserves | |
| Working capital reserve | \$ 318,334 |
| Modernization reserve | 50,838 |
| Machinery replacement reserve | - |
| Fire truck reserve | - |
| Ball diamond reserve | 5,900 |
| ONR crossing reserve | 12,000 |
| Recreation committee reserve | 26,917 |
| Parks and recreation reserve | 6,900 |
| COVID 19 safe restart funding reserve | 14,679 |
| Fire department reserve | 16,749 |
| | 452,317 |

Current Debt

At December 31, 2020 the Township had loans totaling \$637,287. This represents debt related to the replacement of the Road 5 Bailey Bridge which matures in December 2039 and the purchase of a Grader which matures in July 2027. This gives us an Annual Repayment Limit of \$139,782 – which represents 25% of revenues less net debt charges. The Township is currently using 11% of its annual levy to fund debt payment.

Taxation

The Township currently has a levy of \$691,922 which includes about \$10,000 annually toward capital costs. The Township greatly depends on grants to fund its capital program. According to the Ministry of Municipal Affairs and Housing the average residential household pays \$1635 which makes up 2.6% of a median household income. Increasing costs in other areas put a limit on what the Township is able to increase to fund capital costs. Many of its roads are used to service the unorganized Townships adjacent to the municipality and we do not have the ability to tax these properties.

Overall Financial Impact

This financing strategy is fully funded only through a tax increase of 177%. This large increase is due to the small nature of the municipality – 165 households. Unfortunately, the shortfall in infrastructure greatly exceeds the municipalities repayment limit of \$139,782 annually and our operating reserves would not make an impact. This tax rate increase also assumes that the Gas Tax and OCIF funding will

continue at their current rates. The Municipality will balance this budget by temporarily missing service delivery levels while waiting for provincial or federal funding opportunities. Traditionally, large infrastructure projects have been funded through a combination of Federal and Provincial Funding with the municipality putting in 10%. At this rate the municipality would still need a significant tax increase of 20% to cover its 10% share over the longer term.

Table 4-3

Capital Revenue Estimates

| Income | | 2022 |
|-----------|---------|------------|
| Gas Tax | \$ 5 | 21,058.00 |
| OCIF | \$ 5 | 100,000.00 |
| Municipal | \$ 5 | 10,000.00 |
| Total | \$ 5 | 131,058.00 |